

SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Hydrochloric Acid, 31 – 36%

Product Name: Hydrochloric Acid, 31 – 36.7%

Identified Uses: acid etching, steel pickling, oil and gas, ore and mineral, food processing, pharmaceutical, organic chemical synthesis

Company Information:

ASHTA Chemicals Inc.

P.O. Box 858

Ashtabula Ohio 44005

Phone: (440) 997-5221

Fax: (440) 998-0286

24-hour Emergency Phone: CHEMTREC: (800) 424-9300

SECTION 2: HAZARDS IDENTIFICATION

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Corrosive to metals - Category 1 Serious eye damage - Category 1 Skin corrosion - Category 1B

Specific target organ toxicity - single exposure - Category 3

GHS label elements, including precautionary statements:

Signal Word: **Danger**

Pictogram(s):



Hazard Statements

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Precautionary Statements

P234	Keep only in original container.
P261	Avoid breathing dust/ fume/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water. Shower.



P304 + P340 + P310	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
P305 + P351 + P338 + P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P403 + P233	Store in a well-ventilated place. Keep container with a resistant inner liner.
P405	Store locked up.
P406	Store in corrosive resistant stainless steel container with a resistant inner liner.
P501	Dispose of contents/container in accordance with local/state/national regulations.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms:

CHEMICAL NAME: Hydrochloric acid
TRADE NAME: Hydrochloric acid, 31 – 36%
SYNONYMS: Muriatic acid, Chlorohydric acid, Hydrogen Chloride

C.A.S: 7647-01-0
EC: 231-595-7
WHMIS: D2A, E

CHEMICAL FORMULA: HCl (in aqueous solution)
CHEMICAL FAMILY: Inorganic Acid

SECTION 4 FIRST AID MEASURES

Description of first aid measures:

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give humidified air. Give oxygen, but only by a certified physician. Consult a physician.

In case of skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Remove contact lenses if present and easy to do. Continue rinsing eyes during transport to medical facility.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Consult a physician.



SECTION 5 FIRE FIGHTING MEASURES

Flash Point (Method):	Non-combustible.
Extinguishing Media:	Use extinguishing agents compatible with acid and appropriate for the burning material. Use water spray to keep fire-exposed containers cool.
Auto Ignition Temp:	Non-combustible.
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus and full protective clothing. In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials.
Unusual Fire/Explosion Hazards:	Releases flammable hydrogen gas when reacting with metals.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Environmental Precautions:

Use closed systems when possible. Provide local exhaust ventilation where vapor or mist may be generated. Avoid discharge into drains, water courses or onto the ground.

Containment and Cleaning:

Follow preplanned emergency procedures. Only properly equipped, trained, functional personnel should attempt to contain a leak. All other personnel should be evacuated from the danger area. Using full protective equipment, apply appropriate emergency device or other securement technology to stop the leak if possible.

Small Spill:	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. If necessary: neutralize the residue with a dilute solution of sodium carbonate.
Large Spill:	Corrosive liquid. Stop leak if without risk. Do not touch spilled material. Use water spray curtain to knock down vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of sodium carbonate. Be careful that vapor is not present at a concentration level above TLV.

SECTION 7: HANDLING AND STORAGE

Precautions to be taken for handling and storage:

Wear appropriate personal protective equipment. Do not get in eyes, on skin, on clothing. Do not breathe mist or vapor. Observe good industrial hygiene practices. Do not empty into drains. Use caution when combining with water; DO NOT add water to acid, ALWAYS add acid to water while stirring to prevent release of heat, steam and fumes. Store in a well-ventilated place. Store away from incompatible materials. Store closed containers in a clean, cool, open or well ventilated area. Keep out of sun.



SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Principal Component: Hydrochloric Acid

Occupational Exposure Limits:

Regulatory Limits:

Component	OSHA Final PEL TWA	OSHA Final PEL STEL	OSHA Final PEL Ceiling
Hydrochloric Acid Mixture	---	---	5 ppm 7.59 mg/m ³

ACGIH TLV = 5 ppm (7.59 mg/m³) TWA

NIOSH IDLH = 50 ppm (as HCl, 2010)

Exposure Controls:

Eye Protection:

Tightly fitting safety goggles. Face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Other Protection:

Complete suit protecting against chemicals. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Ventilation Recommended:

Exhaust ventilation is required to meet PEL limits.

Glove Type Recommended:

Wear neoprene, nitrile, butyl rubber or PVC gloves to prevent exposure.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

Appearance	Colorless to light yellow liquid
Odor	Pungent (irritating/strong)
Odor Threshold	0.3ppm (can cause olfactory fatigue)
pH	<1 (in aqueous solution)
Melting point/freezing point	-30°C (-22°F)
Initial boiling point	>100°C (>212°F)
Flash point	Not applicable



Auto-ignition Temp	Not applicable
Evaporation rate	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Not combustible
Upper/lower flammability or explosive limits	Not combustible
Water solubility	100%
Molecular Weight	36.46
Relative Density (Specific Gravity)	1.16 (32% HCl solution) 1.19 (36.5% HCl solution)
Bulk Density	8.75 lbs/gal (32% HCl solution) 9.83 lbs/gal (36.5% HCl solution)
Vapor Density (air = 1)	1.267 at 20 °C
Vapor Pressure	84 mm Hg @ 20°C
Partition Coefficient: n-octanol/water	No data available

SECTION 10: STABILITY AND REACTIVITY

- Stability: Hydrochloric acid is stable under normal conditions and pressures.
- Conditions to avoid: Incompatible materials, metals, excess heat, bases.
- Incompatibility: Bases, amines, metals, permanganates, (e.g. potassium permanganate), fluorine, metal acetylides, hexalithium disilicide.
- Hazardous decomposition products: Hydrogen chloride, chlorine, hydrogen gas.
- Polymerization: Hazardous polymerization WILL NOT occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

- Inhalation: Vapors and mist will irritate throat and respiratory system and cause coughing.
- Skin contact: Causes skin burns.
- Eye contact: Causes eye burns.
- Ingestion: Harmful if swallowed. Causes digestive tract burns. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Symptoms related to the physical, chemical and toxicological characteristics:

Contact with this material will cause burns to the skin, eyes and mucous membranes. Permanent eye damage including blindness could result.

Information on toxicological effects:

- Acute toxicity: Harmful if swallowed.
- Skin corrosion/irritation: Causes severe skin burns and eye damage.
- Serious eye damage/eye



Irritation:	Causes serious eye damage.
Respiratory sensitization:	Not available.
Skin sensitization:	No data available.
Germ cell mutagenicity:	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity:	This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.
Reproductive toxicity:	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure:	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure:	No data available.
Aspiration hazard:	Not available.
Chronic effects:	Prolonged inhalation may be harmful.

Components Species Test Results:

Hydrochloric acid (CAS# 7647-01-0)

Rat - Inhalation LC ₅₀ :	3124 ppm, (1 hour)
Rabbit - Dermal LD ₅₀ :	5010 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Because of the low pH of this product, it would be expected produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.
Aquatic Toxicity:	This material is toxic to fish and aquatic organisms. Most aquatic species do not tolerate pH lower than 5.5 for any extended period.
Fish Toxicity:	Fish LC ₅₀ Mosquito fish: 282 mg/l, 96 hours Fish LC ₅₀ Bluegill: 3.6 mg/l, 48 hours
Persistence and degradability:	Not biodegradable. Hydrochloric acid will likely be neutralized to chloride by alkalinity present in natural environment..
Bioaccumulative Potential:	No data available.
Mobility in soil:	Hydrochloric acid will be neutralized by naturally occurring alkalinity. The acid will permeate soil, dissolving some soil material and will then neutralize.
Other adverse effects:	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)

SECTION 13: DISPOSAL CONSIDERATIONS

Collect and reclaim or dispose in sealed containers at a properly licensed waste disposal site. This material , if not neutralized, must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national or international regulations.



SECTION 14: TRANSPORT INFORMATION

Shipping:

Usual Shipping Containers: Tank cars, bulk tankers.
Usual Shelf Life: Indefinite (life of containers).
Storage/Transport Temperatures: Ambient.

Suitable Storage:

Materials/Coatings: Teflon, Tygon, Rubber, PVC and polypropylene materials.

D.O.T. Information:

Labeling: Corrosive
D.O.T. Identification Number: UN 1789
D.O.T. Shipping Name: Hydrochloric Acid
Hazard Class: 8
Packing Group: II
Hazard Guide: 157
Placard: UN 1789

SECTION 15 REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

Hydrochloric Acid CAS#: 7647-01-0

SARA 311/312 Hazards

Acute health hazard, reactive hazard.

Massachusetts Right To Know Components

Hydrochloric Acid CAS#: 7647-01-0

Pennsylvania Right To Know Components

Hydrochloric Acid CAS#: 7647-01-0

New Jersey Right To Know Components

Hydrochloric Acid CAS#: 7647-01-0

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

OSHA PSM/RMP Threshold for Accidental Release:

CAS# 7647-01-0 is regulated under OSHA PSM *only* if anhydrous HCl.



CAS# 7647-01-0 is regulated under EPA RMP *only* if $\geq 37\%$ HCl.

Toxic Substances Control Act (TSCA):

Hydrochloric Acid

CAS#: 7647-01-0

Comprehensive Environmental Response Compensation Liability Act: (CERCLA)

Hydrochloric Acid

CAS#: 7647-01-0

SECTION 16

OTHER INFORMATION

NFPA Rating:

Health hazard: 3

Fire Hazard: 0

Reactivity Hazard: 1

This information is drawn from recognized sources believed to be reliable. ASHTA Chemicals, Inc. Makes no guarantees or assumes any liability in connection with this information. The user should be aware of changing technology, research, regulations, and analytical procedures that may require changes herein. The above data is supplied upon the condition that persons will evaluate this information and then determine its suitability for their use. Only U.S.A regulations apply to the above.

Version 1.0	For the new GHS SDS Standard	Revision Date: 12/31/2014
Version 1.1	Graphics updated	Revision Date: 3/9/2015
Version 1.2	Title updated	Revision Date: 6/2/2015
Version 1.3	Section 9 changes	Revision Date: 7/30/2015
Version 1.4	Section 1, 15 changes	Revision Date: 4/15/2016
Version 1.5	Changed P501 text (Section 2)	Revision Date: 6/15/2016
Version 1.6	Updated Section 2.0	Revision Date 4/20/2017